

Material Safety Data Sheet

Revision Date Prepared by Technical Information

July 6, 2012 Kai Hui 1-800-201-8822 or <u>support@mgchemicals.com</u>

Head Office Emergency

9347 - 193 Street, Surrey, B.C., V4N 4E7 Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

Section 1: Product Identification

MSDS Code: 4860-4865 Name: No Clean Leaded Solder Sn 63 Pb 37 Related Part Numbers: 4860-18G; 4865-227G, 4865-454G, 4866-227G, and

4867-227G Use: Soldering

Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
7439-92-1	Lead	35.3-37.09	0.15 mg/m ³	0.05 mg/m^3	N/E
7440-31-5	Tin	60.44-62.8	2.00 mg/m^3	2.00 mg/m^3	N/E

Section 3: Hazards Identification

Eyes: Fumes may cause eye irritation.

Skin: Fumes may cause skin irritation.

Inhalation: Inhalation of the fumes from this or other soldering products may cause headache, nausea, and

muscular pain.

Ingestion: Ingestion of the fumes from this or other soldering products may cause headache, nausea, and

nuscular pain.

Chronic: Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness,

constipation and abdominal pain.

Section 4: First Aid Measure

Eyes: MOLTEN PRODUCT: Cool burns with plenty of low-pressure water. Get immediate medical attention.

SOLID PRODUCT: Remove any contact lenses. Immediately flush eyes with large quantities of water

for at least 15 minutes. Get medical attention if irritation develops.

Skin: MOLTEN PRODUCT: Immediately cool skin burns with water and cold packs for at least 15 minutes. Do

not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. SOLID PRODUCT: Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

Inhalation: If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek

medical attention.

Ingestion: If person is conscious, immediately give 2 glasses of water. Do not induce vomiting. Get immediate

medical attention.

Section 5: Fire Fighting Measures

Autoignition Temperature: N/A Flash Point: N/A LEL / UEL: N/E

Extinguishing Media: Alcohol foam, carbon dioxide, or dry chemical

General Information: Closed containers may explode when exposed to fire conditions.

Section 6: Accidental Release Measures

PAGE 1 / 4 MSDS Code: 4860-4867



Spill Procedure: If the material is in its solid state, pick up and reuse. When molten, allow to solidify, and the

reuse if it is not contaminated. If contaminated, refer to section 13 for disposal information.

Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do

not expose container to heat or flame.

Storage: Do not store or use near sparks or open flames. Keep containers tightly closed and pright when not in

use in order to prevent leakage.

Section 8: Exposure Controls

Routes of entry: Eyes, Ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure

limits.

Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective Personal

Protection: clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

Section 9: Physical and Chemical Properties

Physical Solid Odor: Solubility Slight **Evaporation** N/E None

in water: State: Rate:

Boiling Specific Water=1@25°C N/E 1380°C Vapor 1mmHq Vapor pH: N/A

Point: 2516°F Pressure: @866°C Gravity: Varies according Density:

to Composition.

Section 10: Stability and Reactivity

Stability: Stable under ordinary use and storage conditions. Incompatibilities: Strong acids and strong oxidizers should be avoided. Polymerization: Will not occur under normal use and storage conditions.

Decomposition: May emit toxic fumes of carbon monoxide and carbon dioxide.

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure) No.

Carcinogenicity: (risk of cancer) Lead: IARC-2B-Possibly carcinogenicity to humans.

Teratogenicity: (risk of malformation in an unborn fetus) No

The CCOHS lists lead as being reproductively toxic. Reproductive Toxicity: (risk of sterility)

Mutangenicity: (risk of inheritable genetic effects) No.

Inhalation Inhalation Lethal Exposure Ingestion Skin (LC50): (LD50): (LD50): Concentrations: (TCLo):

20 mg/m3/6H/30D Lead N/A N/A N/A

(intermittent)

Tin N/A N/A N/A N/A

Section 12: Ecological Information

General Information:

Volatile Organic Compounds, % by weight: N/A Volatile Organic Compounds, grams per litre: N/A

Section 13: Disposal Information

PAGE 2 / 4 MSDS Code: 4860-4867



General Information:

Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, Sate / Provincial, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

Section 14: Transportation Information

Ground:

Not-regulated

Air:

Not-regulated

Sea:

Not-regulated

Section 15: Regulatory Information

CANADA

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

DSL

All ingredients in this product are listed on the Domestic Substances List

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling regulations.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance.

WHMIS

This product belongs to the following categories: N/A

USA

CAA (Clean Air Act, USA)

This product does not contain any class 1-ozone depletors.

This product does not contain any class 2-ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

This product contains Lead 37.09 % (CAS# 7439-92-1) toxic chemicals subject to the reporting requirements of section 313 of Title III of the superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains the following chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372: Lead 37.09 % (CAS# 7439-92-1)

TSCA (Toxic Substances Control Act of 1976, USA)


All substances are TSCA listed.

California Proposition 65 (Chemicals know to cause cancer or reproductive toxicity, May 1, 1997 revision, USA) This product contains lead a chemical known to the state to cause reproductive toxicity and cancer.

HMIS RATING

		_
HEALTH:	2	
FLAMMABILITY:	0	0
PHYSICAL HAZARD:	0	
PERSONAL PROTECTION:		

NFPA RATING





EUROPE

RoHS

This product contains lead, therefore does not comply with European RoHS regulations.

WEEE

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

Definitions: N/A = not applicable, N/E = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes

the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and

handling the product in accordance with federal, state, and local regulations.

PAGE 4 / 4 MSDS Code: 4860-4867