

Material Safety Data Sheet

Revision Date Prepared by **Technical Information**

November 9, 2010 Patti Rogers 1-800-201-8822 or support@mgchemicals.com

Head Office Emergency 9347 - 193 Street, Surrey, B.C., V4N 4E7 Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

Section 1: Product Identification

MSDS Code: 8234 - liquid Name: Fiber Optic Cleaner

Related Part Numbers: 8234-500ML

Use: Fiber Optic Cleaner

Section 2: Hazardous Ingredients

CAS# **ACGIH TWA** Osha Pel Osha Stel **Chemical Name** Percentage by weight 67-63-0 2-propanol >99% 400ppm 400ppm 500ppm

Section 3: Hazards Identification

WHMIS Codes: B2, D2B

NFPA Ratings: Health 1 Flammability Reactivity 0 Reactivity 0 HMIS Ratings: Health 1 Flammability 3

May cause eye irritation, characterized by a burning sensation, redness, tearing, inflammation, and Eyes:

possible corneal injury.

Skin: May cause skin irritation with pain and stinging, especially if skin is abraded.

May cause respiratory tract irritation. Inhaling high concentrations may cause central nervous system Inhalation:

effects characterized by headache, and dizziness.

Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting, and diarrhea. May Ingestion:

cause central nervous system depression.

Chronic: Skin contact over a long period of time may cause dermatitis.

Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush eyes with plenty of water. Get medical aid if irritation persists.

Skin: Wash skin with plenty of soap and water. Get medical aid if symptoms persist. Remove contaminated

clothing.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing

is difficult, give oxygen. Get medical aid.

Ingestion: Do not induce vomiting. Give milk or water. Get medical aid immediately.

Section 5: Fire Fighting Measures

Autoignition 425°C Flash Point: 12°C **LEL / UEL**: 2 / 12 Temperature:

Extinguishing Use water spray, dry chemical, carbon dioxide, or chemical foam.

General Will burn if involved in a fire. Vapors can travel to a source of ignition and flash back. This product is

Information: an explosion hazard.



Section 6: Accidental Release Measures

Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection. Spill Procedure: Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further

residue with paper towel and place in container. Wash spill area with soap and water.

Section 7: Handling and Storage

Handling: Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use. Avoid breathing vapors

and prolonged or repeated contact with skin. Vapors may accumulate and travel to distant ignition sources

and flashback. Provide adequate ventilation.

Keep away from sources of ignition. Store in a cool, dry, well-ventilated area, away from incompatible Storage:

substances.

Section 8: Exposure Controls

Routes of Eyes, ingestion, inhalation, and skin.

entry:

Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure

Personal Protection:

Ventilation:

Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when adequate ventilation or local

exhaust ventilation to keep airborne concentrations below exposure limits cannot be achieved.

Wear impervious gloves, vitron or nitrite.

Section 9: Physical and Chemical Properties

Evaporation 1.5 **Physical** Liquid Odor: Alcohol Solubility: Completely

State: Rate: (ether=1)

Boiling 82°C Specific 0.79 Vapor 40mmHg **Vapor** 2.1(Air=1) pH: N/a

Point: Gravity: Pressure: @23.8°C Density:

Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures.

Conditions to

Incompatibilities:

avoid:

Temperatures over 40°C, ignition sources, and incompatible substances.

Strong oxidizers, acetaldehyde, chlorine, ethylene oxide, acids and isocyanates, hydrogen +

palladium, nitroform, oleum, phosgene, oxygen, aluminum, aluminum triisopropoxide,

trinitromethane, barium perchlorate, tetrafluoroborate, chromium trioxide, sodium dichromate

+ sulfuric acid.

Polymerization: Will not occur.

Decomposition: Carbon monoxide, carbon dioxide, acrid smoke and fumes.

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure) Repeated skin contact may cause defatting of the skin resulting

in dermatitis.

Carcinogenicity: (risk of cancer) No Teratogenicity: (risk of malformation in an

unborn fetus)

No

Reproductive Toxicity: (risk of sterility) No

Mutangenicity: (risk of heritable genetic effects)

Inhalation 16000 ppm/8h Ingestion 3600 mg/kg **Lethal Exposure** Skin N/e Concentrations: (LD50): (rat) (LC50): (rat) (LD50):



Section 12: Ecological Information

General Avoid runoff into storms and sewers, which lead into waterways. Water runoff can cause

Information: environmental damage.

Environmental Impact Data: (percentage by weight)

CFC: 0 **HFC**: 0 **CI.Solv**: 0 **VOC**: 100 **HCFC**: 0 **ODP**: 0

Section 13: Disposal Information

General Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff

Information: can cause environmental damage.

Section 14: Transportation Information

Ground:

Classified as **CONSUMER COMMODITY**, **ORM-D**. Refer to USA CFR 49 regulations and Canadian Transportation of Dangerous Goods Regulations

Air:

Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations.

This product is permitted as "Dangerous Goods in Excepted Quantities". Refer to IATA Section 2.7. The total net quantity contained each outer package is limited to a maximum of three 50-pack cartons. Large Quantities:

Shipping Name: Isopropanol, UN number: 1219, Class: 3, Packing group: II, Flash point: 12°C.

Subsidiary Risk-nil, Recommend using original MG Chemicals certified outer cartons. Tape all seams on the carton. Hazard Label Required-Flammable Liquid. A double arrow orientation label is required and is already printed on the original outer carton.

Sea - All Sizes:

Shipper must be trained and certified. Refer to IATA regulations.

Shipping Name: Isopropanol, UN number: 1219, Class: 3, Packing group: II, Flash point: 12°C.

Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations. SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

This product contains >99% of 2-propanol (CAS# 67-63-0), a toxic chemical subject to the reporting requirements.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does contain>99% % of 2-propanol (CAS# 67-63-0) a chemical subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain any chemicals listed as hazardous air pollutants.

California Proposition 65 (Chemicals know to cause cancer or reproductive toxicity, May 1, 1997 revision, USA)

This product does not contain any chemicals listed.

Health Canada


Labeling and containers used in this product are listed in compliance with Consumer Chemicals and Container regulations.

Environment Canada

Chemicals in this product are listed on the Domestic Substances List in the Canadian Environmental Protection Act

This product does not contain any ozone depleting substances.

PAGE 3 / 4 MSDS Code: 8234 - Liquid





Industry and Science Canada

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

RoHS (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.

Section 16: Other Information

Definitions: N/a = not applicable, n/e = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the

information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in

accordance with federal, state, and local regulations.

PAGE 4 / 4 MSDS Code: 8234 - Liquid