

# **Material Safety Data Sheet**

Revision Date Prepared by Technical Information

October 23, 2007 Patti Rogers 1-800-201-8822 or <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a>

Head Office Emergency

9347 - 193 Street, Surrey, B.C., V4N 4E7 Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

#### Section 1: Product Identification

MSDS Code: 402B - aerosol Name: Super Duster 152

Related Part Numbers: 402B-340G, 402B-450G

Use: For removing microscopic dust.

#### Section 2: Hazardous Ingredients

CAS# Chemical Name Percentage by weight ACGIH TWA Osha Pel Osha Stel

75-37-6 1,1-Difluoroethane 99% n/e n/e n/e

## Section 3: Hazards Identification

WHMIS Codes: A

NFPA Ratings: Health 1 Flammability 4 Reactivity 1
HMIS Ratings: Health 1 Flammability 4 Reactivity 1

Eyes: Contact with eye may cause severe tissue damage because of frostbite.

**Skin:** Contact with liquid or escaping vapor can cause frostbite, indicated by pallor or redness, loss of

sensation, and swelling.

Inhalation: Deliberate Inhalation of high concentrations of vapor should be avoided as it is harmful.

Deliberate inhalation, may result in cardiac symptoms, unconsciousness or death. This product is not recommended for intentional misuse or deliberate inhalation as death without warning may occur. When oxygen levels in air are reduced to 12% - 14% symptoms of asphyxiation will

occur: loss of coordination, increased pulse rate, and deeper respiration.

**Ingestion:** Aspiration hazard. May cause irritation of the digestive tract.

Chronic: Over exposure may cause dizziness and loss of concentration. At higher levels, CNS depression

and cardiac arrhythmia may result from exposure.

## Section 4: First Aid Measure

Eyes: Immediately bathe (do not rub) any frostbite with lukewarm (not hot) water. In the absence

of water, cover with soft wool or other suitable material. Contact a physician for any low

temperature burns from liquid contact.

**Skin:** Immediately bathe (do not rub) any frostbite with lukewarm (not hot) water. In the absence

of water, cover with soft wool or other suitable material. Contact a physician for any low

temperature burns from liquid contact.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical aid.

**Ingestion:** Improbable due to low boiling point (-25°C).

PAGE 1 / 4 MSDS Code: 402B - Aerosol



#### Section 5: Fire Fighting Measures

Autoignition Temperature: 454°C Flash Point: -50°C LEL / UEL: 3.9/16.9

**Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or chemical foam.

General Information: WARNING: Do not hake or tilt during use as flammable liquid may be dispensed. Do

not use near potential sources of ignition, open flames, hot surfaces or live electrical

appliances. Containers may explode in the heat of a fire.

#### Section 6: Accidental Release Measures

Spill Procedure: Avoid breathing vapors. Ventilate area thoroughly.

# Section 7: Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing. Do not inhale. Do not expose container to heat or flame.Storage: Keep away from direct sunlight, heat, and sources of ignition. Store in a cool, dry, well ventilated area.

# **Section 8: Exposure Controls**

Routes of entry: Eyes, ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below

exposure limits.

**Personal** Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate

**Protection:** protective clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

## Section 9: Physical and Chemical Properties

Physical Gas Odor: ethereal Solubility: 0.27% Evaporation

State: Rate: (ether=1)

Boiling -26.2°C Specific 0.99g/cc Vapor 86 PSI Vapor 2.4(Air=1) pH: 7

Point: Gravity: Pressure: @21°C Density:

#### Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures. Do not mix with oxygen or air above

atmospheric pressure. Any source of high temperature, such as lit cigarettes, flames, or

welding may yield toxic and/or corrosive decomposition products.

Conditions to avoid: Temperatures over 40°C, ignition sources, and incompatible materials.

Incompatibilities: Alkali and alkaline earth metals, powdered aluminum, zinc, magnesium, and beryllium.

Polymerization: Will not occur.

Decomposition: Halogens, halogen acids, possibly carbonyl halides. This material can decompose at high

temperatures.

#### Section 11: Toxicological Information

**Sensitization:** (effects of repeated exposure)

No effects known. Cardiac sensitization occurred in dogs exposed to 150,000 ppm.

Carcinogenicity: (risk of

cancer)

The ingredients of this product are not classified as being carcinogenic by ACGIH (American Conference of Governmental industrial Hygienists) or IARC (International Agency for Research on Cancer), not regulated as carcinogens by OSHA (Occupational Safety and Health Administration), and not listed as carcinogens by NTP (National

Toxicology Program)



**Teratogenicity:** (risk of malformation in an unborn

fetus)

Reproductive Toxicity: N/e

(risk of sterility)

**Mutangenicity:** (risk of heritable genetic effects)

Unknown

N/e

eritable genetic effects)

Lethal Exposure Concentrations:

Ingestion(LD50): n/e Inhalation(LC50): N/e Skin(LD50): n/e

# Section 12: Ecological Information

General Information: Avoid runoff into storms and sewers, which lead into waterways. Water runoff can cause

environmental damage.

Environmental Impact Data: (percentage by weight)

CFC: 0 HFC: 100 CI.Solv.: 0 VOC: 0 HCFC: 0 ODP: 0

#### Section 13: Disposal Information

General Information: Dispose of in accordance with all local, provincial, state, and federal regulations. Water

runoff can cause environmental damage.

#### **Section 14: Transportation Information**

#### Ground:

Consumer Commodity, ORM-D

#### Air:

Cannot be shipped by air.

#### Sea:

Limited quantity, 1,1-Difluoroethane, UN#1030, Class 2.1. Shipper must be trained and certified. Refer to IMDG regulations.

# Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain any chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

# Section 15: Regulatory Information Cont'd

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depletors.

This product does not contain any class 2 ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.

PAGE 3 / 4 MSDS Code: 402B - Aerosol



California Proposition 65 (Chemicals know to cause cancer or reproductive toxicity, May 1, 1997 revision, USA)

This product does not contain any chemicals listed.

#### **Health Canada**

Labeling and containers used in this product are listed in compliance with Consumer Chemicals and Container regulations. This product is not defined as flammable by Consumer Chemicals and Container Regulations (Canada) and by 1500.3 (C)(6). 16 CFR, Fed. Haz. Substance Act, C.P.S.P. Regs. (USA) HOWEVER, THIS PRODUCT CAN BE IGNITED UNDER CERTAIN CIRCUMSTANCES.

#### **Environment Canada**

Chemicals in this product are listed on the Domestic Substances List in the Canadian Environmental Protection Act

This product does not contain any ozone depleting substances.

#### **Industry and Science Canada**

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

**RoHS** (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.

#### **Section 16: Other Information**

**Definitions:** n/a = not applicable, n/e = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the

information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in

accordance with federal, state, and local regulations.

PAGE 4 / 4 MSDS Code: 402B - Aerosol