

Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By:		Waterford Plant 260 Hudson River Rd Waterford NY 12188			
Revised:		03/22/2010			
Preparer:		PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS			
CHEMTREC		1-800-424-9300			
Chemical Family/Use:		Sealant			
Formula:		MixtureSilicone sealant			
HMIS					
Flammability:	1	Reactivity:	0	Health:	1
		-			
NFPA					
Flammability:	1	Reactivity:	0	Health:	2
•		•			

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! May be harmful if swallowed. Irritating to eyes, respiratory system and skin. Adverse liver and reproductive effects reported in animals.

Form: paste Color: black Odor: vinegar-like

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed.

SKIN

Uncured product contact will irritate lips, gums and tongue. Skin irritation is possible after contact with the uncured product.

INHALATION

Inhalation of vapors may cause irritation of the respiratory tract. Applies in uncured state.

EYES

Eye irritation is possible after contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

Liver; Reproductive hazard



Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

dermal; Eyes

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS REG NO.	<u>WGT. %</u>	
A. HAZARDOUS			
Methyltriacetoxysilane	4253-34-3	1 - 5 %	
Octamethylcyclotetrasiloxane	556-67-2	1 - 5 %	
B. NON-HAZARDOUS Dimethylpolysiloxane Treated Filler Siloxanes & Silicones, Dimethylpolymers w/Methylsilsesquioxanes	70131-67-8 68611-44-9 68554-67-6	60 - 100 % 10 - 30 % 5 - 10 %	

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

SKIN

Wash with soap and water. Get medical attention if irritation or symptoms from Section 3 develop.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.



Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT: METHOD: IGNITION TEMPERATURE: FLAMMABLE LIMITS IN AIR - LOWER (%): FLAMMABLE LIMITS IN AIR - UPPER (%): > 93.3 °C; 200 °F estimated Unknown not applicable not applicable

No

SENSITIVITY TO MECHANICAL IMPACT:

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Product releases acetic acid during application and curing. Use mechanical ventilation to stay below TLV of 10 ppm acetic acid. Avoid contact with skin and eyes. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation.

STORAGE

Keep containers tightly closed in a cool, well-ventilated place.



Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers; Exhaust ventilation

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Solvent-resistant gloves (butyl-rubber)

EYE AND FACE PROTECTION

Safety glasses with side-shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
Octamethylcyclotetras iloxane	556-67-2	Z_INTL_OELREL	5 ppm

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F: VAPOR PRESSURE (20 C) (MM HG): VAPOR DENSITY (AIR=1): FREEZING POINT: PHYSICAL STATE: ODOR: COLOR: EVAPORATION RATE (BUTYL ACETATE=1): SPECIFIC GRAVITY (WATER=1): DENSITY: ACID / ALKALINITY (MEQ/G): pH: not applicable Unknown no data available not applicable paste vinegar-like black < 1 ca. 1.06 ca. 1.06 ca. 1.06 g/cm3 Unknown not applicable

Page 4/8



Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

SOLUBILITY IN WATER (20 C): SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): VOLATILE ORGANIC CONTENT: VOC EXCL. H2O & EXEMPTS (G/L): Unknown Toluene

2.4 %(m) 26 g/l

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO2); Carbon monoxide; Acetic acid.; Silicon dioxide.; formaldehyde; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: no data available

ACUTE DERMAL

Remarks: no data available

ACUTE INHALATION

Remarks: no data available

OTHER

Octamethylcyclotetrasiloxane Ingestion: Rodents given large doses via oral gavage of octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size). Inhalation: In inhalation studies, laboratory rodents exposed to octamethylcyclotetrasiloxane (300 ppm five days week, 90 days)developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liverweights returned to normal. Microscopic examination of the liver cells did not show





Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

any evidence of pathology. Inhalationstudies utililizing laboratory rabbits and guinea pigs showed no effects on liver weights. Inhalation exposures typical ofindustrial usage (5-10 ppm) showed no toxic effects in rodents. Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestationand lactation) with octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were found. Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 daysprior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live meanlitter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300ppm dosing levels. Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of theseeffects are limited to the 700 ppm exposure group. These results have been shown to be rat-specific. Further studies are ongoing. In developmental toxicity studies, rats and rabbits were exposed to octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

SENSITIZATION

no data available

SKIN IRRITATION

no data available

EYE IRRITATION

no data available

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Ecotoxicological data for this product is not available.

DISTRIBUTION no data available CHEMICAL FATE no data available

MOMENTIVE

Material Safety Data Sheet

Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Canada DSL Inventory	y (positive listing)				
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)				
Korea Existing Chemicals	y (positive listing)				
Inventory (KECI)) (1				
China Inventory of Existing	y (positive listing)				
Chemical Substances					
Australia Inventory of Chemical	y (positive listing)				
Substances (AICS)	/				
Philippines Inventory of Chemicals	y (positive listing)				
and Chemical Substances					
(PICCS)	·· (nonitive listing)				
EU list of existing chemical substances	y (positive listing)				
	· (Nexative listing)				
Canada NDSL Inventory	n (Negative listing)				
TSCA list	y (positive listing)	On TSCA Inventory			
For inventories that are marked as quantity restricted or special cases, please contact Momentive.					

US Regulatory Information

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Page 7/8



Version: 1.9 03/22/2010

RTV 103 - black ACETOXY SEALANT (black)

Canadian Regulatory Information

WHMIS HAZARD CLASS

- D2A Very Toxic Material Causing Other Toxic Effects
- D2B Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are NEGL = negligible EST = estimated appropriate., C = ceiling limitNF = none found NA UNKN = unknown NE = none established REC = recommended ND = none = not applicable determined V = recommended by vendor SKN = skin TS = trade secret R = MST = mist NT = not tested recommended STEL = short term exposure limit ppm = parts ppb = parts per billion By-product= reaction by-product, TSCA inventory status not per million required under 40 CFR part 720.30(h-2).